

SUSPENSION SETUP

RAZE TRAIL

Fork: RockShox 35 Gold 29 RL, 150mm

Follow RockShox 35 Gold 29 RL recommended settings on the bottom right back side of the casting. Mondraker recommended RockShox 35 Gold 29 RL fork settings based on rider weight and Trail application:

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	70	open	5
129,8-136,4lbs / 59-62 kg	77	open	5
138,6-145,2lbs / 63-66 kg	84	open	5-4
147,4-154lbs / 67-70 kg	91	open	5-4
156,2-162,8lbs / 71-74 kg	98	open	5-4
165-171,6lbs / 75-78 kg	105	open	4-3
173,8-180,4lbs / 79-82 kg	112	open	4-3
182,6-189,2lbs / 83-86 kg	119	open	4-3
191,4-198lbs / 87-90 kg	126	open	3-2
200,2-206,8lbs / 91-94 kg	133	open	3-2
209-215,6lbs / 95-98 kg	140	open	3-2
217,8-224,4lbs / 99-102 kg	147	open	2-1
226,6-233,2lbs / 103-106 kg	154	open	2-1
235,4-242lbs / 107-110 kg	161	open	2-1
244,2-250,8lbs / 111-114 kg	168	open	1
>253-319lbs / >115-145 kg	175	open	1

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Fox Float DPS LV EVOL Performance

SAG		RECOMMENDED SETTING	
RIDER WEIGHT	AIR PRESURE	CLICS OUT FROM FULLY CLOSED	
lbs / kg	psi	LSC	LSR
<121-128lbs / <55-58 kg	100	open	11
129,8-136,4lbs / 59-62 kg	108	open	11-10
138,6-145,2lbs / 63-66 kg	116	open	11-10
147,4-154lbs / 67-70 kg	124	open	10-9
156,2-162,8lbs / 71-74 kg	132	open	10-9
165-171,6lbs / 75-78 kg	140	open	9-8
173,8-180,4lbs / 79-82 kg	148	open	9-8
182,6-189,2lbs / 83-86 kg	156	open	8-7
191,4-198lbs / 87-90 kg	164	open	8-7
200,2-206,8lbs / 91-94 kg	172	open	7-6
209-215,6lbs / 95-98 kg	180	open	7-6
217,8-224,4lbs / 99-102 kg	188	mid	6-5
226,6-233,2lbs / 103-106 kg	196	mid	4-3
235,4-242lbs / 107-110 kg	204	mid	3-2
244,2-250,8lbs / 111-114 kg	212	mid	2-1
>253-319lbs / >115-145 kg	220	mid	1

*Settings based on Downhill application and 30-35% recommended sag