

SUSPENSION SETUP

SUPERFOXY R SUPER ENDURO

Fork: Öhlins RXF 38 M.2 29, 170mm

Follow Öhlins RXF36 M.2 recommended settings on the bottom right back side of the casting.
Mondraker recommended Öhlins RXF36 M.2 fork settings based on rider weight and Super Enduro application:

SAG		RECOMMENDED SETTING		
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED		
lbs / kg	psi	HSC	LSC	LSR
<121-128lbs / <55-58 kg	70/170	4	15	15
129,8-136,4lbs / 59-62 kg	76/170	4	14	14
138,6-145,2lbs / 63-66 kg	82/180	4	13	13
147,4-154lbs / 67-70 kg	88/180	4	12	12
156,2-162,8lbs / 71-74 kg	94/180	4	11	11
165-171,6lbs / 75-78 kg	100/190	4	10	10
173,8-180,4lbs / 79-82 kg	106/190	4	9	9
182,6-189,2lbs / 83-86 kg	112/200	4	8	8
191,4-198lbs / 87-90 kg	118/200	4	7	7
200,2-206,8lbs / 91-94 kg	124/210	3	6	6
209-215,6lbs / 95-98 kg	130/210	3	5	5
217,8-224,4lbs / 99-102 kg	136/220	3	4	4
226,6-233,2lbs / 103-106 kg	142/220	3	3	3
235,4-242lbs / 107-110 kg	148/230	3	2	2
244,2-250,8lbs / 111-114 kg	154/230	3	1	1
>253-319lbs / >115-145 kg	160/230	3	1	1

*Suggested fork sag 20%

These values offer a general recommendation. Rebound and compression damping settings are a personal choice and should be fine-tuned depending on the riding style and terrain conditions.

Rear shock: Öhlins TTX Air

SAG		RECOMMENDED SETTING		
RIDER WEIGHT	AIR PRESSURE	CLICS OUT FROM FULLY CLOSED		
lbs / kg	psi	HSC	LSC	LSR
<121-128lbs / <55-58 kg	120	3	10	12
129,8-136,4lbs / 59-62 kg	128	3	10	12-11
138,6-145,2lbs / 63-66 kg	136	3	10	11-10
147,4-154lbs / 67-70 kg	144	3	9	11-10
156,2-162,8lbs / 71-74 kg	152	3	9-8	10-9
165-171,6lbs / 75-78 kg	160	3	9-8	10-9
173,8-180,4lbs / 79-82 kg	168	3	8-7	9-8
182,6-189,2lbs / 83-86 kg	176	3	8-7	9-8
191,4-198lbs / 87-90 kg	184	3	7-6	8-7
200,2-206,8lbs / 91-94 kg	192	3	7-6	8-7
209-215,6lbs / 95-98 kg	200	3	6-5	7-6
217,8-224,4lbs / 99-102 kg	208	2	6-5	7-6
226,6-233,2lbs / 103-106 kg	216	2	5-4	6-5
235,4-242lbs / 107-110 kg	224	2	5-4	6-5
244,2-250,8lbs / 111-114 kg	232	2	3	5-4
>253-319lbs / >115-145 kg	240	2	3	4

*Settings based on Downhill application and 30-35% recommended sag