

# CHASER 750, GRAPHITE/BLACK, 2022

obj. č.: 010.22296



Doporučená cena

**155.999 Kč**

## Technické specifikace

<b>vyráběné velikosti</b> S: 380mm / M: 420mm / L: 450mm / XL: 490mm	<b>hmotnost</b> 24,8 Kg
<b>rám</b> Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard	<b>vidlice</b> Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload
<b>hlavové složení</b> Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°	<b>přehazovačka</b> Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1
<b>řazení</b> Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click	<b>brzdové páčky</b> Sram G2 R, tool-free reach adjust
<b>kličky</b> Race Face Aeffect ebike, 165mm	<b>řídítka</b> Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
<b>představec</b> Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore	<b>sedlovka</b> Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm
<b>sedlo</b> FIZIK Terra Aidon X5 145mm	<b>náboj přední</b> Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts
<b>náboj zadní</b> Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts	<b>řetěz</b> Sram SX Eagle, 12s, Powerlock
<b>kazeta</b> Sram PG-1210, 11-50T, 12s	<b>dráty</b> CN round stainless steel
<b>ráfky</b> MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes	<b>pláště</b> Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead
<b>a151</b> 010.22296	<b>obj.c.</b> 010.22296

**gripy**

Onoff Diamond, 1lock-on, 135mm

**tlumič**

RockShox Deluxe Select R Debonair, 205x65mm. Settings: Low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

**přední brzda**

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

**zadní brzda**

Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

**nastavení tlumiče**

Light compression, Light rebound, 1 Token

**převodník**

Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

**patka k přehazovačce**

Mondraker M068

**motor+baterie**

Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3, Bosch Powertube 750Wh, Bosch Kiox 300