# FOXY CARBON RR 29 MIND, MARLIN BLUE/CARBON, 2022

*obj. č: 010.22320*

Doporučená cena
**181.999 Kč**



## Technické specifikace

**vyráběné velikosti**
S: 380mm / M: 420mm / L: 450mm / XL: 500mm

**hmotnost**
13,4 Kg

**rám**
Foxy 29 Stealth Air full Carbon, Zero Suspension System, 150mm travel, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Optional Geometry Kit

**vidlice**
Öhlins RXF 36 M.2 29, 160mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber

**hlavové složení**
Acros custom for 1-1/2

**přehazovačka**
Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

**řazení**
Sram Trigger GX Eagle, 12s, X-Actuation 1:1

**brzdové páčky**
Sram G2 RS, SwingLink, tool-free reach adjust

**kliky**
Sram GX Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

**středové složení**
Sram DUB BSA, sealed bearings, 73mm

**řidítka**
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

**představec**
Onoff Sulfur FG 30mm, 6061 forged alloy, 31.8mm barbore

**sedlovka**
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

**sedlo**
SDG BEL-AIR 3.0, LPU foam, steel rails

**náboj přední**
DT 350, Boost 15x110mm, IS 6 bolts

**náboj zadní**
DT 350, Boost 12x148mm, 36T SL Ratchet system, IS 6 bolts, XD freehub

**řetěz**
Sram NX Eagle, 12s, Powerlock

**kazeta**
Sram XG-1275, 10-52T, 12s

**dráty**
DT Competition, straightpull


**pláště**
Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead

**a151**
010.22320

**obj.c.**
010.22320

| | |
|---|---|
| **gripy**<br>Onoff Diamond, 1lock-on, 135mm | **tlumič**<br>Öhlins TTX Air 205x65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 30x8mm bottom bushings |
| **přední brzda**<br>Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads | **zadní brzda**<br>Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads |
| **nastavení tlumiče**<br>C20 compression, R35 rebound | **převodník**<br>32T, CNC-machined alloy, X-SYNC 2 |
| **patka k přehazovačce**<br>Sram UDH | **ostatní**<br>*Optional Geometry kit: steering cups: +/- 1º |

## Geometrie




- A Seat Tube Length
- B Top Tube Length
- C Bottom Bracket Drop
- D Bottom Bracket Height
- E Chainstay Length
- F Seat Tube Angle, Actual
- G Seat Tube Angle, Effective
- H Head Tube Angle
- I Fork Offset
- J Wheelbase
- K Head Tube Length
- L Reach
- M Stack

**ENDURO**
**FOXY CARBON (STANDARD)**

| Size | S | M | L | XL |
|---|---|---|---|---|
| A Seat Tube Length | 375 mm | 415 mm | 445 mm | 500 mm |
| B Top Tube Length | 600 mm | 620 mm | 650 mm | 670 mm |
| C Bottom Bracket Drop | -23 | -23 | -23 | -23 |
| D Bottom Bracket Height | 350 mm | 350 mm | 350 mm | 350 mm |
| E Chainstay Legth | 435 mm | 435 mm | 435 mm | 435 mm |
| F Seat Tube Angle, Actual | 70.5° | 70.5° | 70.5° | 70.5° |
| G Seat Tube Angle, Effective | 76° | 76° | 76° | 76° |
| H Head Tube Angle | 65° | 65° | 65° | 65° |
| I Fork Offset | 44 mm | 44 mm | 44 mm | 44 mm |
| J Wheelbase | 1203 mm | 1227 mm | 1253 mm | 1279 mm |
| K Head Tube Length | 90 mm | 100 mm | 115 mm | 130 mm |
| L Reach | 445 mm | 465 mm | 485 mm | 505 mm |
| M Stack | 615 mm | 623 mm | 637 mm | 651 mm |

**ENDURO**
**FOXY CARBON (LOW)**

| Size | S | M | L | XL |
|---|---|---|---|---|
| A Seat Tube Length | 375 mm | 415 mm | 445 mm | 500 mm |
| B Top Tube Length | 600 mm | 620 mm | 650 mm | 670 mm |
| C Bottom Bracket Drop | -28 | -28 | -28 | -28 |
| D Bottom Bracket Height | 345 mm | 345 mm | 345 mm | 345 mm |
| E Chainstay Legth | 445 mm | 445 mm | 445 mm | 445 mm |
| F Seat Tube Angle, Actual | 70° | 70° | 70° | 70° |
| G Seat Tube Angle, Effective | 75.5° | 75.5° | 75.5° | 75.5° |
| H Head Tube Angle | 64.5° | 64.5° | 64.5° | 64.5° |
| I Fork Offset | 44 mm | 44 mm | 44 mm | 44 mm |
| J Wheelbase | 1210 mm | 1233 mm | 1260 mm | 1286 mm |
| K Head Tube Length | 90 mm | 100 mm | 115 mm | 130 mm |
| L Reach | 440 mm | 460 mm | 480 mm | 500 mm |
| M Stack | 617 mm | 627 mm | 641 mm | 656 mm |

## Fotogalerie



