# F-PODIUM DC CARBON R, GREEN/CARBON/YELLOW, 2021

*obj. č: 010.21053*




Doporučená cena
**176.799 Kč**

## Technické specifikace

| | |
|---|---|
| **barva rámečku**<br>green/carbon/yellow | **vyráběné velikosti**<br>S 390mm / M 420mm / L 470mm / XL 510mm |
| **hmotnost**<br>11,7 Kg | **rám**<br>F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount. |
| **vidlice**<br>Fox 34 29 Float FIT4 EVOL Step Cast Factory Kashima, 120mm, tapered steerer tube,15x110mm Boost axle, offset 44mm. Settings: remote lockout, compression micro-adjustment at low-speed, rebound, air preload | **hlavové složení**<br>Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom |
| **přehazovačka**<br>Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1 | **řazení**<br>Sram Trigger GX Eagle, 12s, X-Actuation 1:1 |
| **brzdové páčky**<br>Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings | **kliky**<br>Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm |
| **středové složení**<br>Sram DUB BSA, sealed bearings, 73mm | **řidítka**<br>Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9 backsweep, 0 upsweep, 31.8mm barbore Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL |
| **představec**<br>MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm | **sedlovka**<br>Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M/L/XL size 387x125mm |
| **sedlo**<br>Fizik Antares R7 | **náboj přední**<br>DT 370, Boost 15x110mm, IS 6 bolts |
| **náboj zadní**<br>DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts, MS freehub | **řetěz**<br>Sram GX Eagle, 12s, Powerlock |
| **kazeta**<br>Sram XG-1275, 10-50T, 12s | **dráty**<br>DT Champion, straightpull |
| **ráfky**<br>DT Swiss XRC1750 Carbon Spline 29, 30mm internal width, hookless, tubeless ready, 28 spokes | **pláště**<br>Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead |

| | |
|---|---|
| **obj.c.**<br>010.21053 | **tlumič**<br>Fox Float DPS SV EVOL Factory Kashima, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings |
| **přední brzda**<br>Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad | **zadní brzda**<br>Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad |
| **omotávka**<br>Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead | **nastavení tlumiče**<br>Firm compression, light rebound, air volume spacer 0.2 |
| **převodník**<br>34T, CNC-machined alloy, X-SYNC 2 | **patka k přehazovačce**<br>Sram UDH |

## Geometrie




**GEOMETRY**

| Size | S | M | L | XL |
|---|---|---|---|---|
| **A** Seat Tube Length | 390 mm | 420 mm | 470 mm | 510 mm |
| **B** Top Tube Length | 583 mm | 603 mm | 629 mm | 654 mm |
| **C** Bottom Bracket Drop | -31 mm | -31 mm | -31 mm | -31 mm |
| **D** Bottom Bracket Height | 337 mm | 337 mm | 337 mm | 337 mm |
| **E** Chainstay Legth | 432 mm | 432 mm | 432 mm | 432 mm |
| **F** Seat Tube Angle, Actual | 70.8° | 70.8° | 70.8° | 70.8° |
| **G** Seat Tube Angle, Effective | 75.1° | 75.1° | 75.1° | 75.1° |
| **H** Head Tube Angle | 66.8° | 66.8° | 66.8° | 66.8° |
| **I** Fork Offset | 44 mm | 44 mm | 44 mm | 44 mm |
| **J** Wheelbase | 1146 mm | 1167 mm | 1191 mm | 1217 mm |
| **K** Head Tube Length | 85 mm | 90 mm | 100 mm | 115 mm |
| **L** Reach | 430 mm | 450 mm | 470 mm | 490 mm |
| **M** Stack | 577mm | 582mm | 591 mm | 605mm |