F-PODIUM CARBON R, CARBON/YELLOW/GREEN, 2021

obj. č: 010.21041




Doporučená cena
176.799 Kč

Technické specifikace

barva rámečku carbon/yellow/green	**vyráběné velikosti** S 390mm / M 420mm / L 470mm / XL 510mm
hmotnost 10,8 Kg	**rám** F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.
vidlice Fox 32 29 Float FIT4 EVOL Step Cast Factory Kashima, 100mm, tapered steerer tube,15x110mm Boost axle, remote lockout, offset 44mm. Settings: lockout, compression micro-adjustment at low-speed, rebound, air preload	**hlavové složení** Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom
přehazovačka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	**řazení** Sram Trigger GX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings	**kliky** Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm
středové složení Sram DUB BSA, sealed bearings, 73mm	**řidítka** Onoff Helium Carbon 0.2, rise: 4.8mm, width: 760mm, 9 backsweep, 0 upsweep, 31.8mm barbore Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL
představec MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm	**sedlovka** Onoff Helium Carbon 0-R, diameter 31.6mm, length 400mm
sedlo Fizik Antares R7	**náboj přední** DT 370, Boost 15x110mm, IS 6 bolts
náboj zadní DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts, MS freehub	**řetěz** Sram GX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-50T, 12s	**dráty** DT Champion, straightpull
ráfky DT Swiss XRC1750 Carbon Spline 29, 30mm internal width, hookless, tubeless ready, 28 spokes	**plášť** Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead

obj.c. 010.21041	**tlumič** Fox Float DPS SV EVOL Factory Kashima, 185x47,5mm. Settings: 2 position remote compression (open/lock), low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings
přední brzda Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad	**zadní brzda** Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad
omotávka Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead	**nastavení tlumiče** Firm compression, light rebound, air volume spacer 0.2
převodník 34T, CNC-machined alloy, X-SYNC 2	**patka k přehazovačce** Sram UDH

Geometrie



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	390 mm	420 mm	470 mm	510 mm
B Top Tube Length	580 mm	600mm	625 mm	650 mm
C Bottom Bracket Drop	-40 mm	-40 mm	-40 mm	-40 mm
D Bottom Bracket Height	325 mm	325 mm	325 mm	325 mm
E Chainstay Legth	432 mm	432 mm	432 mm	432 mm
F Seat Tube Angle, Actual	72°	72°	72°	72°
G Seat Tube Angle, Effective	76.5°	76.5°	76.5°	76.5°
H Head Tube Angle	68°	68°	68°	68°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1132 mm	1153 mm	1177 mm	1203 mm
K Head Tube Length	85 mm	90 mm	100 mm	115 mm
L Reach	440 mm	460 mm	480 mm	500 mm
M Stack	570 mm	575 mm	584 mm	598 mm