SUMMUM CARBON RR MX MIND, CARBON/RACING SILVER, 2022

obj. č: 010.22108



Doporučená cena
267.799 Kč

Pokud se chcete cítit jako jeden z našich mezinárodních jezdců, je toto kolo pro vás. S rámem, který je od základu nový, je měřítkem na mezinárodních tratích. Je postaveno s využitím převratných technologií společnosti Mondraker, včetně MIND, systému telemetrie, který vám pomůže vydat ze sebe maximum díky optimalizaci odpružení, systému ZERO SUSPENSION. Kolo se dodává ve dvou variantách, s 29" koly vpředu i vzadu, nebo MX s 29" koly vpředu a 27,5" koly vzadu.

Technické specifikace

vyráběné velikosti
S / M / L / XL 29

hmotnost
15,9 kg

rám
Summum Carbon Stealth Air full Carbon, Zero Suspension System, 200mm travel, Forward Geometry, Carbon Monoblock upper link, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, HHG internal cable routing, MAX. capacity dual raw Enduro bearings, shock mudguard, ISCG 05, custom frame protectors. *Geometry kit included

vidlice
Fox 40 29 Float FIT GRIP2 EVOL Factory Kashima, 203mm, air spring, 1-1/8” steerer tube, 20x110mm axle, offset 56mm. Settings: high and low-speed compression, high and low-speed rebound, air preload

hlavové složení
Onoff Mercurium 1.5 ZS for 1-1/8” steerer tube, 41x30.15x7x45ºx45º ACB sealed bearings, geometry kit cups, external diameter 56mm

přehazovačka
Shimano Saint RD-M820-SS, 10s, Shadow+, short cage

řazení
Shimano Saint SL-M820 10s, low friction multi bearing, instant release, multi release, 2-way release

brzdové páčky
Shimano Saint, ergonomic antiskid lever with servo wave, free stroke and tool less reach adjust

kliky
Shimano Saint M825 Hollowtech II, reinforced steel axle, 165mm

středové složení
Shimano 83mm

řidítka
Renthal Fatbar series 7 alloy, rise: 30mm, width: 800mm, 7º backsweep, 5º upsweep, 31.8mm barbore

představec
Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer

sedlovka
SDG Micro I-Beam SP-951 Carbon, diameter 31.6mm, length 300mm, micro-adjustment

sedlo
SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

náboj přední
e*thirteen Boost 20x110mm, triple-sealed, fully machined aluminum, IS 6 bolts

řetěz
Shimano HG95, 10s

kazeta
Shimano CS-HG500-10, 11-25T, 10s

dráty
e*thirteen custom Hive triple-butted black alloy, alloy nipples, nipple washers

ráfky
e*thirteen LG1 Race Carbon, IW30 29

pláště
Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead, Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead

a151
010.22108

obj.c.
010.22108

gripy
Renthal, double lock-on, kevlar compound, 130mm

tlumič
Fox DHX2 Factory Kashima, 225x70mm. Settings: high and low-speed compression, high and low-speed rebound, spring preload. Super light steel (SLS) spring. Trunnion top mount, 30x8mm bottom bushings

přední brzda
Shimano Saint M820, 4-piston caliper, RT86 203mm 2-piece IS 6 bolts rotor with ICE technology, resin pads with cooler


zadní brzda
Shimano Saint M820, 4-piston caliper, RT86 203mm 2-piece IS 6 bolts rotor with ICE technology, resin pads with cooler

nastavení tlumiče
ECC010 compression, ECR012 rebound. Spring rate: S size 400 lbs, M size 450 lbs, L/XL size 500 lbs

převodník
36T, aluminum, BCD 104, E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider

ostatní
*Geometry kit included: +-1º / +-2º headset cups

Geometrie



A	Seat Tube Length
B	Top Tube Length
C	Bottom Bracket Drop
D	Bottom Bracket Height
E	Chainstay Length
F	Seat Tube Angle, Actual
G	Seat Tube Angle, Effective
H	Head Tube Angle
I	Fork Offset
J	Wheelbase
K	Head Tube Length
L	Reach
M	Stack

DOWNHILL

SUMMUM CARBON MX

	Size	S	M	L	XL
A	Seat Tube Length	400 mm	400 mm	400 mm	400 mm
B	Top Tube Length	577 mm	596 mm	622 mm	647 mm
C	Bottom Bracket Drop	0 mm	0 mm	0 mm	0 mm
D	Bottom Bracket Height	350 mm	350 mm	350 mm	350 mm
E	Chainstay Legth	450/455/460 mm	450/455/460mm	450/455/460 mm	450/455/460 mm
F	Seat Tube Angle, Actual	69°	69°	69°	69°
G	Seat Tube Angle, Effective	77°	77°	77°	77°
H	Head Tube Angle	62,5°	63°	63°	63°
I	Fork Offset	56 mm	56 mm	56 mm	56 mm
J	Wheelbase	1260 mm	1270 mm	1295 mm	1320 mm
K	Head Tube Length	110 mm	110 mm	110 mm	110 mm
L	Reach	427 mm	445 mm	470 mm	495 mm
M	Stack	633 mm	633 mm	633 mm	633 mm

Fotogalerie



