

# PLAY 24, RACING SILVER/BLEU MARLIN, 2023

obj. č. 010.23208

Doporučená cena  
**67.499 Kč**



## Technické specifikace

|                                                                                                                                                                                                                             |                                                                                                                                                                                                                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vyráběné velikosti</b><br>One size: 320mm                                                                                                                                                                                | <b>rám</b><br>Play 24 6061 Alloy Stealth evo, hydroformed tubing, integrated internal non-removable battery, Tapered head tube, HHG internal cable routing, BSA bottom bracket, QR 9mm rear axle, 1x drivetrain compatible |
| <b>vidlice</b><br>RockShox Judy Silver TK 26, 100mm, TurnKey, Solo Air, tapered steerer tube, 9x100mm axle, 30mm steel stanchions, 40mm offset. Settings: compression adjustment at low-speed to lock, rebound, air preload | <b>přehazovačka</b><br>Sram NX, 11s, long cage, X-actuation 1:1                                                                                                                                                            |
| <b>řazení</b><br>Sram trigger NX 11s, X-actuation 1:1                                                                                                                                                                       | <b>brzdové páčky</b><br>Sram Level, tool'd reach adjust, lever pivot bushings                                                                                                                                              |
| <b>kliky</b><br>Samox DM 28T steel, 127mm                                                                                                                                                                                   | <b>středové složení</b><br>BSA, 73mm                                                                                                                                                                                       |
| <b>řídítka</b><br>MDK XC 1.0, 6061 alloy, rise: 25mm, width: 580mm, 9° backsweep, 5° upsweep, 31.8mm barbore                                                                                                                | <b>představec</b><br>Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore                                                                                                                                            |
| <b>sedlovka</b><br>MDK XC 0-R, 6061 T6 Alloy, diameter 31.6mm, length 300mm                                                                                                                                                 | <b>sedlo</b><br>SDG Fly JR                                                                                                                                                                                                 |
| <b>náboj přední</b><br>Formula DC20LW, 9x100mm, cup cone ball bearings, IS 6 bolts                                                                                                                                          | <b>náboj zadní</b><br>Mahle-Ebikemotion X-35                                                                                                                                                                               |
| <b>řetěz</b><br>Sram PC1110 11s, Powerlock                                                                                                                                                                                  | <b>kazeta</b><br>Sram PG 1030 11-42T, 11s                                                                                                                                                                                  |
| <b>dráty</b><br>CN round stainless steel                                                                                                                                                                                    | <b>ráfky</b><br>MDK-XP1 24 TLR, 25mm internal width, tubeless ready, 32 spokes                                                                                                                                             |
| <b>pláště</b><br>Kenda Booster 24x2.4 single compound 30TPI, wire bead                                                                                                                                                      | <b>a151</b><br>010.23208                                                                                                                                                                                                   |
| <b>obj.c.</b><br>010.23208                                                                                                                                                                                                  | <b>gripy</b><br>Onoff Twin, 1lock-on                                                                                                                                                                                       |
| <b>přední brzda</b><br>Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                                                   | <b>zadní brzda</b><br>Sram Level, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad                                                                                                   |
| <b>převodník</b><br>28T, steel                                                                                                                                                                                              | <b>patka k přehazovačce</b><br>Mondraker M073                                                                                                                                                                              |
| <b>motor+baterie</b><br>Mahle-Ebikemotion X-35,Mahle-Ebikemotion Internal 250Wh, Mahle-Ebikemotion                                                                                                                          |                                                                                                                                                                                                                            |

**e-KIDS / YOUTH**  
**PLAY 26 / 24 / 20**

| Size                                | 26      | 24     | 20     |
|-------------------------------------|---------|--------|--------|
| <b>A</b> Seat Tube Length           | 350 mm  | 320 mm | 260 mm |
| <b>B</b> Top Tube Length            | 567 mm  | 517 mm | 475 mm |
| <b>C</b> Bottom Bracket Drop        | -30 mm  | -30 mm | -15 mm |
| <b>D</b> Bottom Bracket Height      | 300 mm  | 280 mm | 240 mm |
| <b>E</b> Chainstay Legth            | 420 mm  | 405 mm | 355 mm |
| <b>F</b> Seat Tube Angle, Actual    | 72°     | 72°    | 72°    |
| <b>G</b> Seat Tube Angle, Effective | 72°     | 72°    | 72°    |
| <b>H</b> Head Tube Angle            | 68°     | 68°    | 68°    |
| <b>I</b> Fork Offset                | 40 mm   | 40 mm  | 40 mm  |
| <b>J</b> Wheelbase                  | 1060 mm | 994 mm | 903 mm |
| <b>K</b> Head Tube Length           | 100 mm  | 100 mm | 100 mm |
| <b>L</b> Reach                      | 390 mm  | 350 mm | 340 mm |
| <b>M</b> Stack                      | 546 mm  | 537 mm | 387 mm |



