CHASER R, MARLIN BLUE/BLACK, 2022

obj. č: 010.22170



Technické specifikace

vyráběné velikosti
S: 380mm / M: 420mm / L: 450mm / XL: 490mm

hmotnost
24,6kg

rám
Chaser 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal non-removable battery, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers, shock mudguard

vidlice
Fox 36 29 Float FIT GRIP EVOL Rythm, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload

hlavové složení
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

přehazovačka
Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

řazení
Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

brzdové páčky
Sram G2 R, tool-free reach adjust

kliky
Race Face Aeffect ebike, 165mm

řidítka
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

představec
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

sedlovka
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

sedlo
FIZIK Terra Aidon X5 145mm

náboj přední
Mavic, Boost 15x110mm, IS 6 bolts

náboj zadní
Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts

řetěz
Sram SX Eagle, 12s, Powerlock

kazeta
Sram PG-1210, 11-50T, 12s

dráty
Mavic J-bend duble butted, contactless lacing

ráfky
Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes

pláště
Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

a151
010.22170


obj.c.
010.22170

gripy
Onoff Diamond, 1lock-on, 135mm

tlumič
Fox Float DPS Performance, 205x65mm. Settings: Compression 3 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings

přední brzda Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	**zadní brzda** Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
nastavení tlumiče Light compression, Light rebound, 1 Token	**převodník** Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD
patka k přehazovačce Mondraker M068	**motor+baterie** Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300

Geometrie



- **A** Seat Tube Length
- **B** Top Tube Length
- **C** Bottom Bracket Drop
- **D** Bottom Bracket Height
- **E** Chainstay Length
- **F** Seat Tube Angle, Actual
- **G** Seat Tube Angle, Effective
- **H** Head Tube Angle
- **I** Fork Offset
- **J** Wheelbase
- **K** Head Tube Length
- **L** Reach
- **M** Stack

e-MTB ENDURO
CHASER

	Size	S	M	L	XL
A	Seat Tube Length	380 mm	420 mm	450 mm	490 mm
B	Top Tube Length	605 mm	625 mm	650 mm	670 mm
C	Bottom Bracket Drop	-25 mm	-25 mm	-25 mm	-25 mm
D	Bottom Bracket Height	336 mm	336 mm	336 mm	336 mm
E	Chainstay Legth	455 mm	455 mm	455 mm	455 mm
F	Seat Tube Angle, Actual	73.5°	73.5°	73.5°	73.5°
G	Seat Tube Angle, Effective	76°	76°	76°	76°
H	Head Tube Angle	65.5°	65.5°	65.5°	65.5°
I	Fork Offset	44 mm	44 mm	44 mm	44 mm
J	Wheelbase	1225 mm	1245 mm	1265 mm	1285 mm
K	Head Tube Length	110 mm	110 mm	130 mm	130 mm
L	Reach	450 mm	470 mm	490 mm	510 mm
M	Stack	622 mm	622 mm	640 mm	640 mm

Fotogalerie



