SUPERFOXY R (SPE), FROST GREEN/BLACK/ÖHLINS YELLOW, 2022

obj. č: 010.22076SPE



Pokud chcete kolo Mondraker super enduro se všemi funkcemi, které potřebujete, abyste si každou jízdu užili naplno, ale karbonový rám není na vrcholu vašeho seznamu priorit, je Superfoxy R to pravé kolo pro vás. Opět jsou zde ty nejlepší komponenty, počínaje odpružením Öhlins, komponenty ONOFF a jeho zakázkovými 29" koly Mavic Deemax ... a co je nejlepší, jeho velkolepý rám je vytvořen z nejlepšího hliníku STEATH ALLOY, který umíme v současné době vyrobit. Velkolepý design, krásné barvy a vše navrženo tak, abyste se dostali na hranici svých možností a nic vás nebrzdilo.

Technické specifikace

vyráběné velikosti
S: 380mm / M: 420mm / L: 470mm / XL: 510mm

hmotnost
16,3 Kg

rám
SuperFoxy 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero Suspension System, 160mm travel, Forward Geometry, one piece Monoblock upper link, SuperBoost 12x157mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, telescopic seatpost internal routing, Max. capacity sealed bearings, ISCG 05

vidlice
Öhlins RXF 38 M.2 29, 170mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber

hlavové složení
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

přehazovačka
Sram NX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

řazení
Sram Trigger SX Eagle, 12s, X-Actuation 1:1

brzdové páčky
Sram G2 RS, SwingLink, tool-free reach adjust

kliky
Truvativ Descendant 7K Eagle, SuperBoost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

středové složení
Sram DUB BSA, sealed bearings, 73mm

řidítka
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore


představec
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

sedlovka
Onoff Pija dropper internal, diameter 31.6mm, S size: 337x100mm, M size 387x125mm, L size: 425x150mm, XL size: 465x170mm

sedlo
SDG BEL-AIR 3.0, LPU foam, steel rails

náboj přední Mavic, Boost 15x110mm, IS 6 bolts	**náboj zadní** Mavic, SuperBoost 12x157mm, ID360 Ratched system, IS 6 bolts
řetěz Sram SX Eagle, 12s, Powerlock	**dráty** Mavic J-bend duble butted
ráfky Mavic Custom Deemax 29, 28mm internal width, Maxtal welded rim, tubeless ready, 28 spokes	**pláště** Maxxis Assegai 29x2.5WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead,Maxxis Dissector 29x2.4WT, tubeless ready, 3C MAXX GRIP compound, DH casing, 60x2TPI, folding bead
a151 010.22076SPE	**obj.c.** 010.22076SPE
gripy Onoff Diamond, 1lock-on, 135mm	**tlumič** Öhlins TTX Air 205X65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings
přední brzda Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads	**zadní brzda** Sram G2 RS, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads
nastavení tlumiče C20 compression, R35 rebound	**převodník** 32T, CNC-machined alloy, X-SYNC 2
patka k přehazovačce Mondraker M068	

Geometrie



A	Seat Tube Length
B	Top Tube Length
C	Bottom Bracket Drop
D	Bottom Bracket Height
E	Chainstay Length
F	Seat Tube Angle, Actual
G	Seat Tube Angle, Effective
H	Head Tube Angle
I	Fork Offset
J	Wheelbase
K	Head Tube Length
L	Reach
M	Stack

SUPER ENDURO
SUPERFOXY

	Size	S	M	L	XL
A	Seat Tube Length	380 mm	420 mm	470 mm	510 mm
B	Top Tube Length	605 mm	625 mm	650 mm	670 mm
C	Bottom Bracket Drop	-20 mm	-20 mm	-20 mm	-20
D	Bottom Bracket Height	350 mm	350 mm	350 mm	350 mm
E	Chainstay Legth	445 mm	445 mm	445 mm	445 mm
F	Seat Tube Angle, Actual	71°	71°	71°	71°
G	Seat Tube Angle, Effective	76°	76°	76°	76°
H	Head Tube Angle	65°	65°	65°	65°
I	Fork Offset	44 mm	44 mm	44 mm	44 mm
J	Wheelbase	1224 mm	1245 mm	1273 mm	1293 mm
K	Head Tube Length	100 mm	110 mm	130 mm	130 mm
L	Reach	450 mm	470 mm	490 mm	510 mm
M	Stack	621 mm	621 mm	639 mm	639 mm

Fotogalerie



