

F-PODIUM CARBON, CARBON/ORANGE/GREY, 2021

obj. č.: 010.21037



Technické specifikace

barva rámečku

carbon/orange/grey

vyráběné velikosti

S 390mm / M 420mm / L 470mm / XL 510mm

hmotnost

10,9 Kg

rám

F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 100mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.

vidlice

Rockshox SID SL Select RL 29, 100mm, Charger, Debonair, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload

hlavové složení

Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom

přehazovačka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

řazení

Sram Trigger SX Eagle, 12s, X-Actuation 1:1

brzdové páčky

Sram Level T, Direct Link actuation, tooled reach adjust, lever pivot bushings

kliky

Truvativ Stylo 6K Eagle, 12s, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm

středové složení

Sram DUB BSA, sealed bearings, 73mm

řídítka

Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9 backsweep, 0 upsweep, 31.8mm barbare Onoff Twin, 1lock-on, 135mm

představec

MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm

sedlovka

Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 31.6mm, length 400mm

sedlo

Fizik Antares R7

náboj přední

DT 370, Boost 15x110mm, IS 6 bolts

náboj zadní

DT 370, Boost 12x148mm, 3 Pawl system, IS 6 bolts, MS freehub

řetěz

Sram SX Eagle, 12s, Powerlock

kazeta

Sram PG-1230, 11-50T, 12s

dráty

DT Champion, straightpull

ráfky

DT Swiss X1900 Spline 29, 25mm internal width, sleeved aluminum, tubeless ready, 28 spokes

pláště

Maxxis Rekon Race 29x2.25, EXO protection, tubeless ready, 120TPI, folding bead

obj.c.
010.21037

tlumič
Rockshox SID Select+ RLR Debonair, 185x47.5mm. Settings: OneLock
2 position remote compression (open/lock), low-speed rebound, air
preload. Trunnion top mount, 22.2x10mm bottom bushings

přední brzda
Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts
one-piece rotor, steel-backed organic pad

zadní brzda
Sram Level T, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece
rotor, steel-backed organic pad


omotávka
Maxxis Rekon Race 29x2.25, EXO protection, tubeless ready,
120TPI, folding bead

nastavení tlumiče
Light compression, medium rebound, Lockout 430, 1 Token

převodník
34T, steel, X-Sync 2

patka k přehazovače
Sram UDH

Geometrie



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	390 mm	420 mm	470 mm	510 mm
B Top Tube Length	580 mm	600 mm	625 mm	650 mm
C Bottom Bracket Drop	-40 mm	-40 mm	-40 mm	-40 mm
D Bottom Bracket Height	325 mm	325 mm	325 mm	325 mm
E Chainstay Length	432 mm	432 mm	432 mm	432 mm
F Seat Tube Angle, Actual	72°	72°	72°	72°
G Seat Tube Angle, Effective	76.5°	76.5°	76.5°	76.5°
H Head Tube Angle	68°	68°	68°	68°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1132 mm	1153 mm	1177 mm	1203 mm
K Head Tube Length	85 mm	90 mm	100 mm	115 mm
L Reach	440 mm	460 mm	480 mm	500 mm
M Stack	570 mm	575 mm	584 mm	598 mm