PODIUM CARBON R, CARBON/YELLOW/GREEN, 2021

obj. č: 010.21025



Doporučená cena
129.999 Kč

Technické specifikace

barva rámečku
carbon/yellow/green

vyráběné velikosti
S 390mm / M 420mm / L 470mm / XL 510mm

hmotnost
8,9 Kg

rám
Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible,

vidlice
Fox 32 29 Float FIT4 EVOL Step Cast Factory Kashima, 100mm, tapered steerer tube,15x110mm Boost axle, remote lockout, offset 44mm. Settings: lockout, compression micro-adjustment at low-speed, rebound, air preload

hlavové složení
Onoff Titan tapered for 1-1/8 to 1-1/2 head tube, ACB sealed bearings, top 41.8x30.5x8x45x45, bottom 51.9x40x8x45x45

přehazovačka
Shimano XT M8100, SGS, Shadow+, 12s

řazení
Shimano SLX M7100, Rapid Fire Plus, 12s

brzdové páčky
Shimano XT M8100, ergonomic antiskid lever with servo wave, tool less reach adjust, free stroke adjust

kliky
Shimano XT M8100 Boost, Hollowtech II, Q-factor 172mm, S size: 170mm, M/L/XL size: 175mm

středové složení
Shimano XT MT800 BSA, 68/73mm

řidítka
Onoff Helium Carbon 0.2, rise: 4.8mm, width: 740mm, 9 backsweep, 0 upsweep, 31.8mm barbore Onoff Twin, 1lock-on, 135mm

představec
MDK, 6061 T6 Alloy, 31.8mm barbore, rise: +/-5, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm

sedlovka
Onoff Helium Carbon 0-R VFLEX, diameter 27.2mm, length 400mm

sedlo
Fizik Antares R7

náboj přední
DT 350, Boost 15x110mm, CenterLock

náboj zadní
DT 350, Boost 12x148mm, 36T SL Ratchet system, CenterLock, MS freehub

řetěz
Shimano Deore M6100, 12s, Quick-link

kazeta
Shimano SLX M7100 10-51T Hyperglide+, 12s

dráty
DT Competition, straightpull

ráfky
DT Swiss XR1700 Spline 29, 25mm internal width, welded aluminum, tubeless ready, 28 spokes


plášť
Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead

obj.c.
010.21025

přední brzda
Shimano XT M8100, MT800 ICE-Tech 160mm CenterLock rotor, resin pads

zadní brzda Shimano XT M8110, MT800 ICE-Tech 160mm CenterLock rotor, resin pads, Flatmount	**omotávka** Maxxis Ikon 29x2.20, 3CMaxx Speed compound, tubeless ready, 120TPI, folding bead
převodník 34T, CNC-machined alloy	**patka k přehazovačce** Sram UDH

Geometrie



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	390 mm	420 mm	470 mm	510 mm
B Top Tube Length	590 mm	611mm	632 mm	650 mm
C Bottom Bracket Drop	-65 mm	-65 mm	-65 mm	-65 mm
D Bottom Bracket Height	305 mm	305 mm	305 mm	305 mm
E Chainstay Legth	430 mm	430 mm	430 mm	430 mm
F Seat Tube Angle, Actual	73°	73°	73°	73°
G Seat Tube Angle, Effective	74.5°	74.5°	74.5°	74.5°
H Head Tube Angle	68.5°	68.5°	68.5°	68.5°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1107 mm	1128 mm	1150 mm	1170 mm
K Head Tube Length	85 mm	90 mm	100 mm	115 mm
L Reach	425 mm	444 mm	463 mm	477 mm
M Stack	598 mm	602 mm	611 mm	625 mm