

SUMMUM R MX, BRITISH RACING GREEN/BLACK/ÖHLINS YELLOW, 2022

obj. č.: 010.22092




Veškeré know-how za 20 let historie značky Mondraker. Model Summit s hliníkovým rámem STEALTH, který byl uveden na trh v minulé sezóně, je stále jedním z nejžádanějších. Je v něm pevně zabudováno veškeré know-how, které jsme získali během dvacetileté historie značky Mondraker. DH kolo, které vás překvapí svou nízkou hmotností. K dispozici ve variantách s 29" koly nebo MX a také ve 4 různých velikostech.

Technické specifikace

vyráběné velikosti S / M / L / XL 29	hmotnost 17,5 Kg
rám Summum 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero suspension system, 200mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, MAX. capacity dual raw Enduro bearings, HHG internal cable routing, ISCG 05. *Optional Geometry kit	vidlice Fox 40 29 Float FIT GRIP EVOL Performance, 203mm, air spring, 1-1/8" steerer tube, 20x110mm axle, offset 56mm. Settings: low-speed compression, low-speed rebound, air preload
hlavové složení Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45°x45° ACB sealed bearings, geometry kit cups, external diameter 56mm	přehazovačka Sram trigger GX DH 7s, X-actuation 1:1
řazení Sram trigger GX DH 7s, X-actuation 1:1	brzdové páčky Sram Code R, tool-free reach adjust
kličky Truvativ Descendant DH, DUB axle, Direct mount chain ring, 165mm	středové složení Sram DUB BSA, sealed bearings, 83mm
řídítka Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore	představec Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer
sedlovka SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment	sedlo SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

náboj přední e*thirteen Boost 20x110mm, triple-sealed, fully machined aluminum, IS 6 bolts	řetěz Sram PC1110 11s, Powerlock
kazeta Sram PG 720 11-25T, 7s	dráty e*thirteen custom Hive triple-buttet black alloy, alloy nipples, nipple washers
ráfky e*thirteen LG1 Plus DH, IW29 29	pláště Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead, Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead
a151 010.22092	obj.c. 010.22092
gripy Onoff Diamond, 1lock-on, 135mm	tlumič Fox DHX2 Performance Elite, 225x70mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings
přední brzda Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	zadní brzda Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
nastavení tlumiče ECC010 compression, ECR012 rebound. Spring rate: S size 400 lbs, M size 450 lbs, L/XL size 500 lbs	převodník 34T, steel, X-SYNC, E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider
patka k přehazovačce Mondraker M068	ostatní *Optional geometry kit: +1° / +2° headset cups

Geometrie



DOWNHILL SUMMUM MX

Size	S	M	L	XL
A Seat Tube Length	400 mm	400 mm	400 mm	400 mm
B Top Tube Length	576 mm	596 mm	621 mm	646 mm
C Bottom Bracket Drop	15 mm	15 mm	15 mm	15 mm
D Bottom Bracket Height	350 mm	350 mm	350 mm	350 mm
E Chainstay Legth	450 mm	450 mm	450 mm	500 mm
F Seat Tube Angle, Actual	69°	69°	69°	69°
G Seat Tube Angle, Effective	77°	77°	77°	77°
H Head Tube Angle	63,5°	63,5°	63,5°	63,5°
I Fork Offset	58 mm	58 mm	58 mm	58 mm
J Wheelbase	1256 mm	1270 mm	1301 mm	1326 mm
K Head Tube Length	112 mm	112 mm	112 mm	112 mm
L Reach	430 mm	450 mm	475 mm	500 mm
M Stack	632 mm	632 mm	632 mm	632 mm

Fotogalerie

