

SUMMUM 29, BLACK/WHITE/RED, 2021

obj. č.: 010.21109



Doporučená cena

98.799 Kč

Technické specifikace

barva rámečku black/white/red	vyráběné velikosti S 400mm / M 400mm / L 400mm / XL 400mm
hmotnost 17,9 Kg	rám Summum 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero suspension system, 200mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, MAX. capacity dual raw Enduro bearings, HHG internal cable routing, ISCG 05. Optional geometry kit: +-1 / +-2 headset cups
vidlice Rockshox Boxxer Select RC 29, 200mm, DebonAir, 1-1/8 steerer tube, Boost 20x110mm axle, offset 56mm. Settings: low-speed compression, rebound, air preload	hlavové složení Onoff Mercurium 1.5 ZS for 1-1/8 steerer tube, 41x30.15x7x45x45 ACB sealed bearings, geometry kit cups, external diameter 56mm
přehazovačka Sram X7, 9s, short cage, X-actuation 1:1	přesmykač E.13 LG1 chain guide + DMB (Direct mount Bashguard) Gen 2 Stealth Idler, Aluminum hardware, adjustable/replaceable lower armature, polycarbonate, ISCG 05, adjustable upper slider
řazení Sram trigger X5, 9s, X-actuation 1:1	brzdové páčky Sram Code R, tool-free reach adjust
kliky Race Face Chester, alloy, 165mm	středové složení Race Face BSA, 73mm
řídítka Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 780mm, 9 backsweep, 5 upsweep, 31.8mm barbore Onoff Desert, 1lock-on, 135mm, sizes: S/M L/XL	představec Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer
sedlovka SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment	sedlo SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides
náboj přední MDK DA4371B-M20, Boost 20x110mm, IS 6 bolts	náboj zadní MDK DA4352B, 12x157mm, sealed bearings, IS 6 bolts
řetěz Sram PC-951, 9s	kazeta Sram PG-950, 11-26T, 9s
dráty CN stainless steel	ráfky MDK-DP1 29, 27mm internal width, 32 holes
pláště Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead	obj.c. 010.21109

tlumič

Fox Van RC Performance, 225x70mm. Settings: low-speed compression, low-speed rebound, spring preload. Trunnion top mount, 30x8mm bottom bushings

zadní brzda

Sram Code R, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

nastavení tlumiče

Light compression, light rebound. Spring rate: S size 400 lbs, M size 400 lbs, L size 450 lbs, XL size 500 lbs

patka k přehazovačce

Mondraker M068

přední brzda

Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads


omotávka

Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead

převodník

36T

Geometrie



GEOMETRY

Size	S	M	L	XL
A Seat Tube Length	400 mm	400 mm	400 mm	400 mm
B Top Tube Length	573 mm	593 mm	618 mm	643 mm
C Bottom Bracket Drop	-20 mm	-20 mm	-20 mm	-20 mm
D Bottom Bracket Height	350 mm	350 mm	350 mm	350 mm
E Chainstay Legth	450 mm	450 mm	450 mm	450 mm
F Seat Tube Angle, Actual	69°	69°	69°	69°
G Seat Tube Angle, Effective	77°	77°	77°	77°
H Head Tube Angle	63.5°	63.5°	63.5°	63.5°
I Fork Offset	58 mm	58 mm	58 mm	58 mm
J Wheelbase	1260 mm	1270 mm	1295 mm	1320 mm
K Head Tube Length	112 mm	112 mm	112 mm	112 mm
L Reach	430 mm	450 mm	475 mm	500 mm
M Stack	632 mm	632 mm	632 mm	632 mm