PRIME R (SPE), CHERRY RED/BLACK, 2022

obj. č: 010.22142SPE



Doporučená cena
119.599 Kč

Technické specifikace

vyráběné velikosti
XS: 380mm / S: 390mm / M: 430mm / L: 470mm / XL: 510mm

hmotnost
22,8 Kg

rám
Prime Xtralite 6061 Full Butted Alloy, Forward Geometry, intenal non-removable battery, tapered head tube, Boost 12x148mm rear axle, integrated dropout speed sensor

vidlice
Marzocchi Z2 29 Rail, 120mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: sweep adjust compression, Low-speed rebound, air preload

hlavové složení
Onoff Saturn tapered for 1-1/8” to 1-1/2” head tube, ACB sealed bearings, top 41x30.2x7x45ºx45º, bottom 51.9x40x8x45ºx45º

přehazovačka
Sram SX Eagle, Type 3 roller bearing clutch, cage lock, long cage, 1x12s, X-actuation 1:1

řazení
Sram Trigger SX Eagle, 12s, X-Actuation 1:1, single click

brzdové páčky
Sram G2 R, tool-free reach adjust

kliky
Race Face Aeffect ebike, 165mm

řidítka
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

představec
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

sedlovka
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

sedlo
FIZIK Terra Aidon X5 145mm

náboj přední
Formula DC711, Boost 15x110mm, sealed bearings, IS 6 bolts

náboj zadní
Formula EHL148 Boost 12x148mm, sealed bearings, IS 6 bolts

řetěz
Sram SX Eagle, 12s, Powerlock

kazeta
Sram PG-1210, 11-50T, 12s

dráty
CN round stainless steel

ráfky
MDK-HP1 29, 30mm internal width, tubeless ready, 32 spokes

pláště
Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead, Maxxis Rekon 29x2.6, tubeless ready, dual compound, EXO protection, 60TPI, folding bead

a151
010.22142SPE

obj.c.
010.22142SPE

gripy
Onoff Diamond, 1lock-on, 135mm

přední brzda
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads


zadní brzda
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

převodník
Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD

patka k přehazovačce
Mondraker M068

motor+baterie
Bosch Performance Line CX Cruise (25Km/h) GEN4 BS3 , Bosch Powertube 750Wh, Bosch Kiox 300

Geometrie



A	Seat Tube Length
B	Top Tube Length
C	Bottom Bracket Drop
D	Bottom Bracket Height
E	Chainstay Length
F	Seat Tube Angle, Actual
G	Seat Tube Angle, Effective
H	Head Tube Angle
I	Fork Offset
J	Wheelbase
K	Head Tube Length
L	Reach
M	Stack

e-MTB TRAIL
PRIME 29

	Size	XS	S	M	L	XL
A	Seat Tube Length	380 mm	390 mm	430 mm	470 mm	510 mm
B	Top Tube Length	600 mm	615 mm	645 mm	670 mm	700 mm
C	Bottom Bracket Drop	-60 mm	-60 mm	-60 mm	-60 mm	-60 mm
D	Bottom Bracket Height	318 mm	318 mm	318 mm	318 mm	318 mm
E	Chainstay Legth	455 mm	455 mm	455 mm	455 mm	455 mm
F	Seat Tube Angle, Actual	73.5°	73.5°	73.5°	73.5°	73.5°
G	Seat Tube Angle, Effective	73.5°	73.5°	73.5°	73.5°	73.5°
H	Head Tube Angle	69°	69°	69°	69°	69°
I	Fork Offset	51 mm	51 mm	51 mm	51 mm	51 mm
J	Wheelbase	1138mm	1153 mm	1183 mm	1210 mm	1240 mm
K	Head Tube Length	110 mm	110 mm	110 mm	130 mm	130 mm
L	Reach	410 mm	425 mm	455 mm	480 mm	505 mm
M	Stack	640 mm	640 mm	640 mm	658 mm	658 mm

Fotogalerie



