

RAZE CARBON RR, DEEP PURPLE/LIGHT BLUE, 2023

obj. č.: 010.23089

Doporučená cena
199.999 Kč



Technické specifikace

vyráběné velikosti S: 380mm / M: 420mm / L: 450mm / XL: 500mm	rám Raze 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors.
vidlice Fox 36 29 Float GRIP2 Factory Kashima, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: high and low-speed compression, high and low-speed rebound, air preload	hlavové složení Acros custom for 1-1/2
přehazovačka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	řazení Sram Trigger GX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram G2 RS, SwingLink, tool-free reach adjust	kliky Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
středové složení Sram DUB BSA, sealed bearings, 73mm	řídítka Onoff Krypton Carbon 1.0, rise: 25mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare
představec Onoff Krypton FG 30mm, CNC, 31.8mm barbare	sedlovka Fox Transfer Factory Kashima internal, diameter 31.6mm, S size: 363.5x125mm, M size: 418.3x150mm, L/XL size: 475.1x175mm
sedlo Fizik Antares R7	náboj přední Infinity hub, Boost 15x110mm, IS 6 bolts
náboj zadní Infinity hub, ID360 freewheel technology, Boost 12x148mm, IS 6 bolts	řetěz Sram GX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-52T, 12s	dráty 24 straight-pull double butted spokes
ráfky Mavic CrossMax XL S, 29 Boost 30mm internal width, hookless, tubeless ready, 24 spokes	pláště Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead / Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead
a151 010.23089	obj.c. 010.23089
gripy Onoff Desert, 1lock-on, 135mm	tlumič Fox Float DPS Factory Kashima EVOL LV, 205x57.5mm. Settings: Compression 3 positions lever, low-speed compression, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings

přední brzda

Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadní brzda

Sram G2 RS, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

nastavení tlumiče

Light compression, light rebound, air volume spacer 0.6


převodník

32T, CNC-machined alloy, X-SYNC 2

patka k přehazovačce

Sram UDH

Geometrie



TRAIL
RAZE CARBON

Size	S	M	L	XL
A Seat Tube Length	375 mm	415 mm	445 mm	500 mm
B Top Tube Length	595 mm	620 mm	645 mm	670 mm
C Bottom Bracket Drop	-30	-30	-30	-30
D Bottom Bracket Height	343 mm	343 mm	343 mm	343 mm
E Chainstay Legth	435 mm	435 mm	435 mm	435 mm
F Seat Tube Angle, Actual	71°	71°	71°	71°
G Seat Tube Angle, Effective	76.5°	76.5°	76.5°	76.5°
H Head Tube Angle	65.5°	65.5°	65.5°	65.5°
I Fork Offset	44 mm	44 mm	44 mm	44 mm
J Wheelbase	1193 mm	1217 mm	1243 mm	1269 mm
K Head Tube Length	90 mm	100 mm	115 mm	130 mm
L Reach	455 mm	475 mm	495 mm	515 mm
M Stack	608 mm	617 mm	631 mm	645 mm



Fotogalerie

