FOXY CARBON R 29 MIND, CHERRY RED/CARBON, 2022

obj. č: 010.22316

Doporučená cena
155.999 Kč



Technické specifikace

vyráběné velikosti
S: 380mm / M: 420mm / L: 450mm / XL: 500mm

hmotnost
14,1 Kg

rám
Foxy 29 Stealth Air full Carbon, Zero Suspension System, 150mm travel, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Optional Geometry Kit

vidlice
Fox 36 29 Float FIT GRIP EVOL Rhythm, 160mm, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: sweep adjust compression, low-speed rebound, air preload

hlavové složení
Acros custom for 1-1/2

přehazovačka
Sram Trigger NX Eagle, 12s, X-Actuation 1:1

řazení
Sram Trigger NX Eagle, 12s, X-Actuation 1:1

brzdové páčky
Sram G2 R, tool-free reach adjust

kliky
Truvativ Descendant 6K Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

středové složení
Sram DUB BSA, sealed bearings, 73mm

řidítka
Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9º backsweep, 5º upsweep, 31.8mm barbore

představec
Onoff Sulfur FG 30mm 0º, 6061 forged alloy, 31.8mm barbore

sedlovka
Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm

sedlo
SDG BEL-AIR 3.0, LPU foam, steel rails

náboj přední
DT 370, Boost 15x110mm, IS 6 bolts

náboj zadní
DT 370, Boost 12x148mm, 18T Ratched LN system, IS 6 bolts

řetěz
Sram NX Eagle, 12s, Powerlock

kazeta
Sram XG-1230, 11-50T, 12s

dráty
DT Champion, straightpull

ráfky
DT Swiss E1900 Spline 29, 30mm internal width, sleeved aluminum, tubeless ready, 28 spokes

pláště
Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead

a151
010.22316

obj.c.
010.22316

gripy
Onoff Diamond, 1lock-on, 135mm

tlumič
Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 30x8mm bottom bushings

přední brzda
Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads

zadní brzda
Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads


nastavení tlumiče
Light compression, light rebound, air volume spacer 0.6

převodník
32T, steel, X-Sync 2

patka k přehazovačce
Sram UDH

ostatní
*Optional Geometry kit: steering cups: +/- 1º

Geometrie



A	Seat Tube Length
B	Top Tube Length
C	Bottom Bracket Drop
D	Bottom Bracket Height
E	Chainstay Length
F	Seat Tube Angle, Actual
G	Seat Tube Angle, Effective
H	Head Tube Angle
I	Fork Offset
J	Wheelbase
K	Head Tube Length
L	Reach
M	Stack

ENDURO
FOXY CARBON (STANDARD)

	Size	S	M	L	XL
A	Seat Tube Length	375 mm	415 mm	445 mm	500 mm
B	Top Tube Length	600 mm	620 mm	650 mm	670 mm
C	Bottom Bracket Drop	-23	-23	-23	-23
D	Bottom Bracket Height	350 mm	350 mm	350 mm	350 mm
E	Chainstay Legth	435 mm	435 mm	435 mm	435 mm
F	Seat Tube Angle, Actual	70.5°	70.5°	70.5°	70.5°
G	Seat Tube Angle, Effective	76°	76°	76°	76°
H	Head Tube Angle	65°	65°	65°	65°
I	Fork Offset	44 mm	44 mm	44 mm	44 mm
J	Wheelbase	1203 mm	1227 mm	1253 mm	1279 mm
K	Head Tube Length	90 mm	100 mm	115 mm	130 mm
L	Reach	445 mm	465 mm	485 mm	505 mm
M	Stack	615 mm	623 mm	637 mm	651 mm

ENDURO
FOXY CARBON (LOW)

	Size	S	M	L	XL
A	Seat Tube Length	375 mm	415 mm	445 mm	500 mm
B	Top Tube Length	600 mm	620 mm	650 mm	670 mm
C	Bottom Bracket Drop	-28	-28	-28	-28
D	Bottom Bracket Height	345 mm	345 mm	345 mm	345 mm
E	Chainstay Legth	445 mm	445 mm	445 mm	445 mm
F	Seat Tube Angle, Actual	70°	70°	70°	70°
G	Seat Tube Angle, Effective	75.5°	75.5°	75.5°	75.5°
H	Head Tube Angle	64.5°	64.5°	64.5°	64.5°
I	Fork Offset	44 mm	44 mm	44 mm	44 mm
J	Wheelbase	1210 mm	1233 mm	1260 mm	1286 mm
K	Head Tube Length	90 mm	100 mm	115 mm	130 mm
L	Reach	440 mm	460 mm	480 mm	500 mm
M	Stack	617 mm	627 mm	641 mm	656 mm

Fotogalerie



